

In The Claims

Please amend claims 2, 10, 13, 16, 19, 31, 34, 37 and 40 as set forth below:

1 1. (Original) A method comprising:
2 copying and saving first pixel values corresponding to a first display screen
3 area;
4 blending the copied first pixel values with second pixel values to generate
5 third pixel values;
6 replacing the original first pixel values with the third pixel values to effectuate
7 display of a non-blocking always visible display;
8 monitoring for display operations that impact the first display screen area;
9 upon detection of such a display operation, replacing said third pixel values
10 with said first pixel values using said saved first pixel values;
11 upon completion of the detected operation, copying and saving fourth pixel
12 values corresponding to the first display screen area;
13 blending the copied fourth pixel values with said second pixel values to
14 generate fifth pixel values;
15 replacing the original fourth pixel values with the fifth pixel values to sustain
16 the non-blocking always visible characteristic of the non-blocking always visible
17 display.

1 2. (Amended) The method of claim 1, wherein the method further comprises
2 marking a buffer holding said third/fifth pixel values changed; and
3 periodically checking to determine if said buffer has been marked
4 changed.

1 3. (Original) The method of claim 1, wherein said monitoring comprises

2 intercepting invocations of display screen memory operations; and
3 determining if targeted display screen areas of the display screen memory
4 operations being invoked intersect with said first screen display area.

1 4. (Original) The method of claim 1, wherein the method further comprises
2 intercepting cursor events associated with said first display screen area; and
3 determining whether the cursor events are to be handled by an application
4 program associated with said non-blocking always visible display or an application
5 program associated with an underlying display window.

1 5. (Original) The method of claim 4, wherein each of said blending is performed
2 in accordance with a then current blending setting, and said determining comprises
3 determining if the current blending setting is greater than a predetermined threshold,
4 favoring contents of said non-blocking always visible display.

1 6. (Original) The method of claim 1, wherein said non-blocking always visible
2 display is a selected one of an on-line data monitor, a tool bar, a logo/mark, and an
3 animated assistant.

1 7. (Original) A method comprising:
2 copying and saving first pixel values corresponding to a first display screen
3 area;
4 blending the copied first pixel values with second pixel values corresponding
5 to a non-blocking always visible display to generate third pixel values;
6 replacing the original first pixel values with the third pixel values to effectuate
7 display of the non-blocking always visible display;
8 intercepting cursor events associated with said first display screen area; and

9 determining whether the cursor events are to be handled by an application
10 program associated with said non-blocking always visible display or an application
11 program associated with an underlying display window, based at least in part on a
12 current blending bias between said non-blocking always visible display and said
13 underlying display windows.

1 8. (Original) The method of claim 7, wherein said blending is performed in
2 accordance with a current blending setting, and said determining comprises
3 determining if the current blending setting is greater than a predetermined threshold,
4 favoring contents of said non-blocking always visible display.

1 9. (Original) The method of claim 7, wherein said non-blocking always visible
2 display is a selected one of an on-line data monitor, a tool bar, a logo/mark, and an
3 animated assistant.

b2
1 10. (Amended) A method comprising:
2 copying and saving first pixel values corresponding to a first display screen
3 area on which a non-blocking always visible on-line data monitor is to be rendered;
4 blending the copied first pixel values with second pixel values corresponding
5 to the non-blocking always visible on-line data monitor to generate third pixel values;
6 and
7 replacing the original first pixel values with the third pixel values to effectuate
8 display of the on-line data monitor with the non-blocking always visible attribute to
9 provide visual differentiation between said on-line data monitor and underlying
10 display windows associated with locally executed application programs.

1 11. (Original) The method of claim 10, wherein the method further comprises

2 monitoring for display operations that impact the first display screen area;
3 upon detection of such a display operation, replacing said third pixel values
4 with said first pixel values using said saved first pixel values;
5 upon completion of said display operation, copying and saving fourth pixel
6 values corresponding to the first display screen area;
7 blending the copied fourth pixel values with said second pixel values to
8 generate fifth pixel values; and
9 replacing the original fourth pixel values with the fifth pixel values to sustain
10 the non-blocking always visible characteristic of the on-line monitor.

b2 12. (Original) The method of claim 10, wherein the method further comprises
2 intercepting cursor events associated with said first display screen area; and
3 determining whether the cursor events are to be handled by an application
4 program associated with said non-blocking always visible on-line data monitor or an
5 application program associated with an underlying display window, based at least in
6 part on a current blending bias between said non-blocking always visible on-line
7 data monitor and underlying display windows.

1 13. (Amended) A method comprising:
2 copying and saving first pixel values corresponding to a first display screen
3 area on which a non-blocking always visible task bar is to be rendered;
4 blending the copied first pixel values with second pixel values corresponding
5 to the non-blocking always visible task bar to generate third pixel values;
6 replacing the original first pixel values with the third pixel values to effectuate
7 display of the task bar with the non-blocking always visible attribute;
8 monitoring for display operations that impact the first display screen area;

9 upon detection of such a display operation, replacing said third pixel values
10 with said first pixel values using said saved first pixel values;
11 upon completion of said display operation, copying and saving fourth pixel
12 values corresponding to the first display screen area;
13 blending the copied fourth pixel values with said second pixel values to
14 generate fifth pixel values; and
15 replacing the original fourth pixel values with the fifth pixel values to sustain
16 the non-blocking always visible characteristic of the task bar.

1 14. (Previously Cancelled)

1 15. (Original) The method of claim 13, wherein the method further comprises
2 intercepting cursor events associated with said first display screen area; and
3 determining whether the cursor events are to be handled by an application
4 program associated with said non-blocking always visible task bar or an application
5 program associated with an underlying display window, based at least in part on a
6 current blending bias between said non-blocking always visible task bar and
7 underlying display windows.

1 16. (Amended) A method comprising:
2 copying and saving first pixel values corresponding to a first display screen
3 area on which a non-blocking always visible logo/mark is to be rendered;
4 blending the copied first pixel values with second pixel values corresponding
5 to the non-blocking always visible logo/mark to generate third pixel values;
6 replacing the original first pixel values with the third pixel values to effectuate
7 display of the logo/mark with the non-blocking always visible attribute;
8 monitoring for display operations that impact the first display screen area;

9 upon detection of such a display operation, replacing said third pixel values
10 with said first pixel values using said saved first pixel values;

11 upon completion of said display operation, copying and saving fourth pixel
12 values corresponding to the first display screen area;

13 blending the copied fourth pixel values with said second pixel values to
14 generate fifth pixel values; and

15 replacing the original fourth pixel values with the fifth pixel values to sustain
16 the non-blocking always visible characteristic of the logo/mark.

1 17. (Previously Cancelled)

1 18. (Original) The method of claim 16, wherein the method further comprises
2 intercepting cursor events associated with said first display screen area; and
3 determining whether the cursor events are to be handled by an application
4 program associated with said non-blocking always visible logo/mark or an
5 application program associated with an underlying display window, based at least in
6 part on a current blending bias between said non-blocking always visible logo/mark
7 and underlying display windows.

1 19. (Amended) A method comprising:

2 copying and saving first pixel values corresponding to a first display screen
3 area on which a non-blocking always visible animated assistant is to be rendered;

4 blending the copied first pixel values with second pixel values corresponding
5 to the non-blocking always visible animated assistant to generate third pixel values;

6 replacing the original first pixel values with the third pixel values to effectuate
7 display of the animated assistant with the non-blocking always visible attribute;

8 monitoring for display operations that impact the first display screen area;

9 upon detection of such a display operation, replacing said third pixel values
10 with said first pixel values using said saved first pixel values;

11 upon completion of said display operation, copying and saving fourth pixel
12 values corresponding to the first display screen area;

13 blending the copied fourth pixel values with said second pixel values to
14 generate fifth pixel values; and

15 replacing the original fourth pixel values with the fifth pixel values to sustain
16 the non-blocking always visible characteristic of the animated assistant.

1 20. (Previously Cancelled)

b2 1 21. (Original) The method of claim 19, wherein the method further comprises
2 intercepting cursor events associated with said first display screen area; and
3 determining whether the cursor events are to be handled by an application
4 program associated with said non-blocking always visible animated assistant or an
5 application program associated with an underlying display window, based at least in
6 part on a current blending bias between said non-blocking always visible animated
7 assistant and underlying display windows.

1 22. (Original) An apparatus comprising:
2 storage medium having stored therein programming instructions designed to
3 copy and save first pixel values corresponding to a first display screen
4 area,
5 blend the copied first pixel values with second pixel values corresponding
6 to a non-blocking always visible display to generate third pixel values,
7 replace the original first pixel values with the third pixel values to
8 effectuate display of the non-blocking always visible display,

9 monitor for display operations that impact the first display screen area,
10 upon detection of such a display operation, replace said third pixel values
11 with said first pixel values using said saved first pixel values,
12 copy and save fourth pixel values corresponding to the first display screen
13 area,
14 blend the copied fourth pixel values with said second pixel values to
15 generate fifth pixel values,
16 replace the original fourth pixel values with the fifth pixel values to sustain
17 the non-blocking always visible characteristic of the non-blocking
18 always visible display; and
19 a processor coupled to the storage medium to execute the programming
20 instruction.

br 1 23. (Amended) The apparatus of claim 22, wherein the programming instructions
2 are further designed to
3 mark a buffer holding said third/fifth pixel values changed, and
4 periodically check to determine if said buffer has been marked changed.

1 24. (Original) The apparatus of claim 22, wherein said programming instructions
2 are designed to
3 intercept invocations of display screen memory operations; and
4 determine if targeted display screen areas of the display screen memory
5 operations being invoked intersect with said first screen display area.

1 25. (Original) The apparatus of claim 22, wherein the programming instructions
2 are further designed to
3 intercept cursor events associated with said first display screen area, and

4 determine whether the cursor events are to be handled by an application
5 program associated with said non-blocking always visible display or an application
6 program associated with an underlying display window.

1 26. (Original) The apparatus of claim 25, wherein said programming instructions
2 are designed to perform each of said blending in accordance with a then current
3 blending setting, and perform said determine by determining if the current blending
4 setting is greater than a predetermined threshold, favoring contents of said non-
5 blocking always visible display.

1 27. (Original) The apparatus of claim 22, wherein said non-blocking always
2 visible display is a selected one of an on-line data monitor, a tool bar, a logo/mark,
3 and an animated assistant.

br
1 28. (Original) An apparatus comprising:
2 storage medium having stored therein programming instructions designed to
3 copy and save first pixel values corresponding to a first display screen
4 area,
5 blend the copied first pixel values with second pixel values corresponding
6 to a non-blocking always visible display to generate third pixel values,
7 replace the original first pixel values with the third pixel values to
8 effectuate display of the non-blocking always visible display,
9 intercept cursor events associated with said first display screen area, and
10 determine whether the cursor events are to be handled by an application
11 program associated with said non-blocking always visible display or an
12 application program associated with an underlying display window,
13 based at least in part on a current blending bias between said non-

14 blocking always visible display and said underlying display windows;
15 and
16 a processor coupled to the storage medium to execute the programming
17 instructions.

1 29. (Original) The apparatus of claim 28, wherein said programming instructions
2 are designed to perform said blend in accordance with a current blending setting,
3 and perform said determine by determining if the current blending setting is greater
4 than a predetermined threshold, favoring contents of said non-blocking always
5 visible display.

b2 1 30. (Original) The apparatus of claim 28, wherein said non-blocking always
2 visible display is a selected one of an on-line data monitor, a tool bar, a logo/mark,
3 and an animated assistant.

1 31. (Amended) An apparatus comprising:
2 storage medium having stored therein programming instructions designed to
3 copy and save first pixel values corresponding to a first display screen
4 area on which a non-blocking always visible on-line data monitor is to
5 be rendered;
6 blend the copied first pixel values with second pixel values corresponding
7 to the non-blocking always visible on-line data monitor to generate
8 third pixel values, and
9 replace the original first pixel values with the third pixel values to
10 effectuate display of the on-line data monitor with the non-blocking
11 always visible attribute to provide visual differentiation between said

12 on-line data monitor and underlying display windows associated with
13 locally executed application programs; and
14 a processor coupled to the storage medium to execute the programming
15 instructions.

1 32. (Original) The apparatus of claim 31, wherein the programming instructions
2 are further designed to

3 monitor for display operations that impact the first display screen area,

4 upon detection of such a display operation, replace said third pixel values
5 with said first pixel values using said saved first pixel values,

6 upon completion of said display operation, copy and save fourth pixel values
7 corresponding to the first display screen area,

8 blend the copied fourth pixel values with said second pixel values to generate
9 fifth pixel values, and

10 replace the original fourth pixel values with the fifth pixel values to sustain the
11 non-blocking always visible characteristic of the on-line monitor.

1 33. (Original) The apparatus of claim 31, wherein the programming instructions
2 are further designed to

3 intercept cursor events associated with said first display screen area, and

4 determine whether the cursor events are to be handled by an application

5 program associated with said non-blocking always visible on-line data monitor or an

6 application program associated with an underlying display window, based at least in

7 part on a current blending bias between said non-blocking always visible on-line

8 data monitor and underlying display windows.

1 34. (Amended) An apparatus comprising:

2 storage medium having stored therein programming instructions designed to
3 copy and save first pixel values corresponding to a first display screen
4 area on which a non-blocking always visible task bar is to be rendered.
5 blend the copied first pixel values with second pixel values corresponding
6 to the non-blocking always visible task bar to generate third pixel
7 values,
8 replace the original first pixel values with the third pixel values to
9 effectuate display of the task bar with the non-blocking always visible
10 attribute
11 monitor for display operations that impact the first display screen area,
12 upon detection of such a display operation, replace said third pixel values
13 with said first pixel values using said saved first pixel values,
14 upon completion of said display operation, copy and save fourth pixel
15 values corresponding to the first display screen area,
16 blend the copied fourth pixel values with said second pixel values to
17 generate fifth pixel values, and
18 replace the original fourth pixel values with the fifth pixel values to sustain
19 the non-blocking always visible characteristic of the task bar; and
20 a processor coupled to the storage medium to execute the programming
21 instructions.

1 35. (Cancelled)

1 36. (Original) The apparatus of claim 34, wherein the programming instructions
2 are further designed to
3 intercept cursor events associated with said first display screen area, and

4 determine whether the cursor events are to be handled by an application
5 program associated with said non-blocking always visible task bar or an application
6 program associated with an underlying display window, based at least in part on a
7 current blending bias between said non-blocking always visible task bar and
8 underlying display windows.

1 37. (Amended) An apparatus comprising:

2 storage medium having stored therein programming instructions designed to
3 copy and save first pixel values corresponding to a first display screen
4 area on which a non-blockinging always visible logo/mark is to be
5 rendered,

6 blend the copied first pixel values with second pixel values corresponding
7 to the non-blockinging always visible logo/mark to generate third pixel
8 values,

9 replace the original first pixel values with the third pixel values to
10 effectuate display of the logo/mark with the non-blocking always visible
11 attribute,

12 monitor for display operations that impact the first display screen area,
13 upon detection of such a display operation, replace said third pixel values
14 with said first pixel values using said saved first pixel values,

15 upon completion of said display operation, copy and save fourth pixel
16 values corresponding to the first display screen area,

17 blend the copied fourth pixel values with said second pixel values to
18 generate fifth pixel values, and

19 replace the original fourth pixel values with the fifth pixel values to sustain
20 the non-blocking always visible characteristic of the logo/mark; and

21 a processor coupled to the storage medium to execute the programming
22 instructions.

1 38. (Cancelled) .

1 39. (Original) The apparatus of claim 37, wherein the programming instructions
2 are further designed to
3 intercept cursor events associated with said first display screen area; and
4 determine whether the cursor events are to be handled by an application
5 program associated with said non-blocking always visible logo/mark or an
6 application program associated with an underlying display window, based at least in
7 part on a current blending bias between said non-blocking always visible logo/mark
8 and underlying display windows.

b2
1 40. (Amended) An apparatus comprising:
2 storage medium having stored therein programming instructions designed to
3 copy and save first pixel values corresponding to a first display screen
4 area on which a non-blocking always visible animated assistant is to
5 be rendered,
6 blend the copied first pixel values with second pixel values corresponding
7 to the non-blocking always visible animated assistant to generate third
8 pixel values,
9 replace the original first pixel values with the third pixel values to
10 effectuate display of the animated assistant with the non-blocking
11 always visible attribute
12 monitor for display operations that impact the first display screen area,

13 upon detection of such a display operation, replace said third pixel values
14 with said first pixel values using said saved first pixel values,
15 upon completion of said display operation, copy and save fourth pixel
16 values corresponding to the first display screen area,
17 blend the copied fourth pixel values with said second pixel values to
18 generate fifth pixel values, and
19 replace the original fourth pixel values with the fifth pixel values to sustain
20 the non-blocking always visible characteristic of the animated
21 assistant; and
22 a processor coupled to the storage medium to execute the programming
23 instructions.

br 1 41. (Cancelled)

1 42. (Original) The apparatus of claim 40, wherein the programming instructions
2 are further designed to
3 intercept cursor events associated with said first display screen area, and
4 determine whether the cursor events are to be handled by an application
5 program associated with said non-blocking always visible animated assistant or an
6 application program associated with an underlying display window, based at least in
7 part on a current blending bias between said non-blocking always visible animated
8 assistant and underlying display windows.
